

Roman Blinds & Accessories



Hunter & Hyland assembles a strong, robust Roman blind system in our Surrey workshop. It complies with BSEN13120 with a functional child safety breakaway that has been tested for both its ability to breakaway and its strength in everyday use. The chain simply slots back into the head rail in the event of it being pulled away. There is no difficult re-attachment, no need for chain breakaway connectors or a wall mounted chain retainer. Just a simple, effective click back into the head rail.

We offer made-to-measure systems, pre-packed kits and individual components, should you prefer to assemble yourself according to individual requirements. The blinds are sleek and durable with a variety of options to suit every blind maker whilst remaining cost effective.

Roman Blinds & Accessories

MADE-TO-MEASURE (MTM) ROMAN BLINDS

Hunter & Hyland Roman blind head rails can be made to your individual requirements. They are robust and durable whilst also being aesthetically pleasing and discreet as part of an assembled blind. You have the choice of 8 metal bead chains and can also select the types of rod you prefer to work with. It complies fully with BSEN13120 with a smart pull away chain that simply clicks straight back into the head rail in the event of it being pulled away. There is no difficult re-attachment, no need for chain breakaway connectors or a wall mounted chain retainer. MTM Roman blinds remove the need to hold stock of all the components and mean you won't have any offcut wastage.



MADE-TO-MEASURE (MTM) ROMAN BLINDS

Image shown details all the elements that will be provided in a super lift Roman blind. There are options to select rods and chains.

Our MTM blind consists of:

- Profile with pre-attached hook tape.
- Child safe pulley housing to comply with BSEN13120 super lift system of 1:4 ratio.
- Cord spools with cord guide and 300cms of 1.3mm lift cord.
- Choice of 8 metal bead chains polished chrome, polished brass, antique brass, antique silver, bronze, black nickel, satin nickel and stainless steel - made to your specific drop requirement. All made from brass or stainless steel, to prevent risk of rusting.
- · Universal smart swivel wall/ ceiling bracket.
- Small white plastic eyelet rings 13mm diameter.
- 38mm sew on loop tape (to attach to face fabric).
- Cord clasps (RBCCS) to comply with BSEN13120 standards regarding child safety.
- For your rods and bottom bars you have three options:
 - Option one Provided with fibreglass rods and white aluminium bottom bar (22mm x 4mm).
 - Option two Provided with chrome plated steel rods and white aluminium bottom bar (22mm x 4mm).
 - Option three Provided with neither rods nor bottom bar- for you to use your own.
 - 1 rod is provided for each 30cm of drop.
- Easy step by step fitting instructions.

Order specification options:

Alternatively, blinds can be supplied without breakaway using either a 1:1 or a 1:4 sidewinder supplied with a wall mounted retainer.

Blind can be supplied with a universal smart click wall/ceiling bracket.

- Blind width (specify if measurement is recess size or actual blind width).
- ✓ Blind drop.
 ✓ Fitting heig
- Fitting height (to comply with BSEN13120 regulations).
- \square Left or right hand control.
- Chain colour.
- Chain drop. Unless specified, the chain will be 15cm less than the
- blind drop so that it will still comply with BSEN13120 regulations.
- Rod and bottom bar preferences.

Technical specifications:

- Maximum width: 300cms.
- Maximum drop: 500cms.
- Maximum blind load weight:
 - Super lift 7kg 1:4 (if you pull the chain 20cm it will rise 5cm).

CORD SPOOLS AND BRACKETS

Made-to-measure length	No. of cord spools	No. of brackets
50-75cm	2	2
75-100cm	3	2
100-125cm	4	3
125-150cm	4	3
150-175cm	5	4
175-200cm	5	4
200-225cm	6	5
225-250cm	6	5
250-275cm	7	6
275-300cm	7	6

Workroom & Supplies



CORD SPOOLS AND BRACKETS





COMPONENTS Product code Description Stock unit Dimensions Other info White powder coated aluminium (can be cut with Head rail with hook 5.8m RBS041 35mm x 37mm tape attached Length hacksaw) 5.8m Silver aluminium (can be cut **RBS042** Square drive rod 5mm x 5mm Length with hacksaw) Cord spool with **RBS043** Each 300cm of corc Top or face fix. White powder Swivel lock universal Backplate coated steel. Requires 6g RBS044 Each bracket 27mm x 24mm screws (not supplied) Top or face fix. White powder Spring click universal Backplate **RBS045** Each coated steel. Requires 6g . 37mm x 26mm bracket screws (not supplied) 1.3mm 100% polyester RBS046 Polyester lift cord 500m Reel diameter Child safe sidewinder RBS047 Each Includes cap for opposite end control 1:4Super lift **RBS049** Basic sidewinder Each Includes cap for opposite end (NOT SHOWN) control 1:4 Super lift RBS050 Basic sidewinder Each Includes cap for opposite end (NOT SHOWN) control 1:1 Speedy lift 140mm x Includes 7 day timer. White **RBS051** Remote control Each 60mm with wall mount. 100g per metre length. Zinc RBSTEELROD 4mm Steel rod plated steel. Can be cut with 4mm diameter 3m Length . hacksaw 4mm White fibreglass 24g per metre length. Can be RBFIBREROD 6m Length 4mm diameter cut with hacksaw rod 24g per metre length. Can 4mm Economy be cut with hacksaw. Same 844 4mm diameter 6m Length fibreglass rod quality as standard rod but slight green hue Aluminium bottom 240g per metre length. Can be **RB023** 5m Length 22mm x 4mm cut with hacksaw weight bar **RB016C** Small clear eyelet ring Bag of 100 13mm x 8mm Strong polycarbonate Small white evelet ring Bag of 100 **RB016W** 13mm x 8mm Strong polycarbonate Economy Roman blind Required to be BS13120 RBCC Each 21mm x 16mm cord clasp compliant Roman blind cord Required to be BS13120 RBCCS Each 21mm x 13mm clasp with sew on loop compliant Required if using RBS049 or RBCT 21mm x 41mm Roman blind chain tidy Each RBS050. BS13120 child safety (NOT SHOWN) x 15mm compliant 38mm sew on loop 03LW38 25m Roll tape Polished brass bead 4.5mm Bead Made from brass- will not rust. RB111025PB 125m Reel chain diameter 20kg minimum breaking strain Polished chrome bead 4.5mm Bead Made from brass- will not rust. RB111022PC 125m Reel chain diameter 20kg minimum breaking strain Satin nickel bead 4.5mm Bead Made from brass- will not rust. **RB111021SN** 125m Reel chain diameter 20kg minimum breaking strain Black nickel bead 4.5mm Bead 20kg minimum breaking strain **RB111027BN** 125m Reel chain diameter Antique brass bead 4.5mm Bead RB111029AB 125m Reel 20kg minimum breaking strain . chain diameter 4.5mm Bead RB111026BZ Bronze bead chain 125m Reel 20kg minimum breaking strain diameter Antique silver bead 4.5mm Bead RB111028AS 125m Reel 20kg minimum breaking strain chain diameter 4.5mm Bead RB11100055 150m Reel 20kg minimum breaking strain Stainless steel chain (NOT SHOWN) diameter Unique design- chain can Joining pliers for bead **BBPI IFBS** Each be cut and joint using 1 pair chain of pliers

Alternative chain lengths for pre-packed blinds:

- RB075SS - Endless loop of stainless steel chain: 75cm

RB075SS - Endless loop of stainless steel chain: 100cm

RB125SS - Endless loop of stainless steel chain: 125cm

- RB150SS - Endless loop of stainless steel chain: 150cm





PRE-PACKED ROMAN BLIND KITS

Hunter & Hyland have created a complete pre-packed blind system that contains everything you will need to make a beautiful Roman blind. It contains all the same components as would be provided in a Made-to-measure Roman blind. It complies fully with BSEN13120 with a smart pull away chain that simply clicks straight back into the head rail in the event of it being pulled away. There is no difficult re-attachment, no need for chain breakaway connectors or a wall mounted chain retainer.

The pre-packed kit comes complete with:

- Profile with pre-attached hook tape.
- Child safe pulley housing to comply with BSEN13120.
- · Bead chain- 1m drop standard length. Stainless Steel
- Universal smart swivel wall/ ceiling bracket.
- · Small white plastic eyelet rings. 13mm diameter.
- 38mm sew on loop tape (to attach to face fabric).
- Cord clasp (RBCCS) to comply with BSEN13120 standards regarding child safety.
- 7 x rods.
- White aluminium bottom bar (22mm x 4mm).
- Easy step-by-step fitting instructions.

PRE-PACKED ROMAN BLIND SIZES

Further information to consider:

· Pre-packed Roman blinds can be cut to size with a hacksaw.

Technical specifications:

Maximum blind load weights: — Super lift – 7kg - 1:4 (if you pull the chain 20cm it will rise 5cm).

Code	Description	No. of cord spools	No. of brackets	Cord drop	Chain drop*
RBS060SU	60cm super lift pre-packed Roman blind kit	2	2	300cm	100cm
RBS090SU	90cm super lift pre-packed Roman blind kit	3	2	300cm	100cm
RBS120SU	120cm super lift pre-packed Roman blind kit	4	3	300cm	100cm
RBS150SU	150cm super lift pre-packed Roman blind kit	4	3	300cm	100cm
RBS180SU	180cm super lift pre-packed Roman blind kit	5	4	300cm	100cm
RBS240SU	240cm super lift pre-packed Roman blind kit	6	5	300cm	100cm

* Alternative chains of 75cm, 125cm and 150cm can be purchased separately.







ELECTRICALLY OPERATED BLINDS

Within the MTM roman blind hardware offering, Hunter & Hyland also offer the option for electrically operated blinds. These are provided with all the same hardware as the MTM blind kits, but are also supplied with everything you need to operate your blind via a remote control.

- Max blind weight 4kg.
 Max width 200cm/ 5 cord spools
 Fitted "Forest" tubular motor 24v/16w 0.8NM
 Supplied with adapter and UK plug
 Remote control contains timer and can control up to 15 blinds
 10 year guarantee



TECHNICAL DIAGRAMS AND DATA


When you receive your Roman blind kit or components, you will also receive our Roman Blind System instruction sheet. This will take you through all the steps to not only ensure you have a fully child safety compliant blind system, but to also give you hints and tips to use all the elements to their optimum. The head rail is easy to assemble and fit and the instruction guide will cover any questions you might have throughout the processes of making and fitting your blind. Technical information to note:


- The brackets supplied are designed to be able to be either wall (face) fixed or ceiling (top) fixed.
- The chain and cog are designed to breakaway from the main head rail if a force of 6kg or greater is applied. It can be re-inserted with a simple push and click.
- To maintain compliance with BSEN13120 regarding child safety; cord breakaways must be fitted if the distance between each fold is greater than 200mm (supplied with both made-to-measure and pre-packed kits).
- The chain drop has to be a minimum of 60cm from the floor to maintain compliance with BSEN13120.


The following diagrams show the headrail and bracket dimensions:

HEADRAIL DIMENSIONS

SPRING CLICK UNIVERSAL BRACKET DIMENSIONS SWIVEL LOCK UNIVERSAL BRACKET DIMENSIONS









Hunter & Hyland Ltd

201 – 205 Kingston Road Leatherhead Surrey KT22 7PB

Tel: +44(0)1372 378511 Fax: +44(0)1372 370038 Email: sales@hunterandhyland.co.uk Website: www.hunterandhyland.co.uk

All trade enquiries from new clients should be accompanied by a PDF or fax of your company letterhead or business card.

Trade counter

Perfect for customers who want to choose and purchase products instantly. Help and advice is readily available.

Opening hours: between 8:30-13:00 and 14:00-16:45, Monday to Friday.

Delivery

We operate a small fleet of vans for deliveries in London and the South East. For all other areas, we provide a next day service via a trusted courier.

> Hunter & Hyland Ltd T. +44(0)1372 378511 201-205 Kingston Road F. +44(0)1372 370038

Leatherhead, Surrey sales@hunterandhyland.co.uk KT22 7PB www.hunterandhyland.co.uk



APPOINTMENT TO MAJESTY THE QUEEN PLIERS OF RTAIN RAILS AND IOLSTERY FITTINGS

