

# Roman Blinds & Accessories



Hunter & Hyland assembles a strong, robust Roman blind system in our Surrey workshop. It complies with BSEN13120 with a functional child safety breakaway that has been tested for both its ability to breakaway and its strength in everyday use. The chain simply slots back into the head rail in the event of it being pulled away. There is no difficult re-attachment, no need for chain breakaway connectors or a wall mounted chain retainer. Just a simple, effective click back into the head rail.

We offer made-to-measure systems, pre-packed kits and individual components, should you prefer to assemble yourself according to individual requirements. The blinds are sleek and durable with a variety of options to suit every blind maker whilst remaining cost effective.





#### MADE-TO-MEASURE (MTM) ROMAN BLINDS

Image shown details all the elements that will be provided in a super lift Roman blind. There are options to select rods and chains.

#### Our MTM blind consists of:

- Profile with pre-attached hook tape.
- Child safe pulley housing to comply with BSEN13120 super lift system of 1:4 ratio.
- Cord spools with cord guide and 300cms of 1.3mm lift cord.
- Choice of 8 metal bead chains polished chrome, polished brass, antique brass, antique silver, bronze, black nickel, satin nickel and stainless steel - made to your specific drop requirement. All made from brass or stainless steel, to prevent risk of rusting.
- Universal smart swivel wall/ ceiling bracket.
- Small white plastic eyelet rings 13mm diameter.
- 38mm sew on loop tape (to attach to face fabric).
- Cord clasps (RBCCS) to comply with BSEN13120 standards regarding child safety.
- For your rods and bottom bars you have three options:
  - Option one Provided with fibreglass rods and white aluminium bottom bar (22mm x 4mm).
  - Option two Provided with chrome plated steel rods and white aluminium bottom bar (22mm x 4mm).
  - Option three Provided with neither rods nor bottom bar- for you to use your own.
- 1 rod is provided for each 30cm of drop.
- Easy step by step fitting instructions.

#### Order specification options:

Alternatively, blinds can be supplied without breakaway using either a 1:1 or a 1:4 sidewinder supplied with a wall mounted retainer.

Blind can be supplied with a universal smart click wall/ceiling bracket.

- $\square$ Blind width (specify if measurement is recess size or actual blind width).
- Blind drop.
- $\sqrt{}$ Fitting height (to comply with BSEN13120 regulations).
- $\overline{ }$ Left or right hand control.
- $\sqrt{}$ Chain colour.
- Chain drop. Unless specified, the chain will be 15cm less than the blind drop so that it will still comply with BSEN13120 regulations.
- $\sqrt{}$ Rod and bottom bar preferences.

#### Technical specifications:

- Maximum width: 300cms.
- Maximum drop: 500cms.
- Maximum blind load weight:
  - Super lift 7kg 1:4 (if you pull the chain 20cm it will rise 5cm).

#### CORD SPOOLS AND BRACKETS

Made-to-measure length	No. of cord spools	No. of brackets
50-75cm	2	2
75-100cm	3	2
100-125cm	4	3
125-150cm	4	3
150-175cm	5	4
175-200cm	5	4
200-225cm	6	5
225-250cm	6	5
250-275cm	7	6
275-300cm	7	6



# RBS041 RBS043 RBS045 RBS044 RBS047



# CORD SPOOLS AND BRACKETS COMPONENTS

Product code	Description	Stock unit	Dimensions	Other info		
RBS041	Head rail with hook tape attached	5.8m Length	35mm x 37mm	White powder coated aluminium (can be cut with hacksaw)		
RBS042	Square drive rod	5.8m Length	5mm x 5mm	Silver aluminium (can be cut with hacksaw)		
RBS043	Cord spool with 300cm of cord	Each				
RBS044	Swivel lock universal bracket	Each	Backplate 27mm x 24mm	Top or face fix. White powder coated steel. Requires 6g screws (not supplied)		
RBS045	Spring click universal bracket	Each	Backplate 37mm x 26mm	Top or face fix. White powder coated steel. Requires 6g screws (not supplied)		
RBS046	Polyester lift cord	500m Reel	1.3mm diameter	100% polyester		
RBS047	Child safe sidewinder control 1:4Super lift	Each		Includes cap for opposite end		
RBS049 (NOT SHOWN)	Basic sidewinder control 1:4 Super lift	Each		Includes cap for opposite end		
RBS050 (NOT SHOWN)	Basic sidewinder control 1:1 Speedy lift	Each		Includes cap for opposite end		
RBS051	Remote control	Each	140mm x 60mm	Includes 7 day timer. White with wall mount.		
RBSTEELROD	4mm Steel rod	3m Length	4mm diameter	100g per metre length. Zinc plated steel. Can be cut with hacksaw		
RBFIBREROD	4mm White fibreglass rod	6m Length	4mm diameter	24g per metre length. Can be cut with hacksaw		
844	4mm Economy fibreglass rod	6m Length	4mm diameter	24g per metre length. Can be cut with hacksaw. Same quality as standard rod but slight green hue.		
RB023	Aluminium bottom weight bar	5m Length	22mm x 4mm	240g per metre length. Can be cut with hacksaw		
RB016C	Small clear eyelet ring	Bag of 100	13mm x 8mm	Strong polycarbonate		
RB016W	Small white eyelet ring	Bag of 100	13mm x 8mm	Strong polycarbonate		
RBCC	Economy Roman blind cord clasp	Each	21mm x 16mm	Required to be BS13120 compliant		
RBCCS	Roman blind cord clasp with sew on loop	Each	21mm x 13mm	Required to be BS13120 compliant		
RBCT (NOT SHOWN)	Roman blind chain tidy	Each	21mm x 41mm x 15mm	Required if using RBS049 or RBS050. BS13120 child safety compliant		
03LW38	38mm sew on loop tape	25m Roll				
RB111025PB	Polished brass bead chain	125m Reel	4.5mm Bead diameter	Made from brass- will not rust. 20kg minimum breaking strain		
RB111022PC	Polished chrome bead chain	125m Reel	4.5mm Bead diameter	Made from brass- will not rust. 20kg minimum breaking strain		
RB111021SN	Satin nickel bead chain	125m Reel	4.5mm Bead diameter	Made from brass- will not rust. 20kg minimum breaking strain		
RB111027BN	Black nickel bead chain	125m Reel	4.5mm Bead diameter	20kg minimum breaking strain		
RB111029AB	Antique brass bead chain	125m Reel	4.5mm Bead diameter	20kg minimum breaking strain		
RB111026BZ	Bronze bead chain	125m Reel	4.5mm Bead diameter	20kg minimum breaking strain		
RB111028AS	Antique silver bead chain	125m Reel	4.5mm Bead diameter	20kg minimum breaking strain		
<b>RB11100055</b> (NOT SHOWN)	Stainless steel chain	150m Reel	4.5mm Bead diameter	20kg minimum breaking strain		
RBPLIERS	Joining pliers for bead chain	Each		Unique design- chain can be cut and joint using 1 pair of pliers		

#### Alternative chain lengths for pre-packed blinds:

- RB075SS Endless loop of stainless steel chain: 75cm
- RB075SS Endless loop of stainless steel chain: 100cm
- RB125SS Endless loop of stainless steel chain: 125cm
- RB150SS Endless loop of stainless steel chain: 150cm





#### PRE-PACKED ROMAN BLIND KITS

Hunter & Hyland have created a complete pre-packed blind system that contains everything you will need to make a beautiful Roman blind. It contains all the same components as would be provided in a Made-to-measure Roman blind. It complies fully with BSEN13120 with a smart pull away chain that simply clicks straight back into the head rail in the event of it being pulled away. There is no difficult re-attachment, no need for chain breakaway connectors or a wall mounted chain retainer.

#### The pre-packed kit comes complete with:

- · Profile with pre-attached hook tape.
- · Child safe pulley housing to comply with BSEN13120.
- Bead chain- 1m drop standard length. Stainless Steel
- Universal smart swivel wall/ ceiling bracket.
- Small white plastic eyelet rings. 13mm diameter.
- 38mm sew on loop tape (to attach to face fabric).
- Cord clasp (RBCCS) to comply with BSEN13120 standards regarding child safety.
- 7 x rods.
- White aluminium bottom bar (22mm x 4mm).
- Easy step-by-step fitting instructions.

#### Further information to consider:

Pre-packed Roman blinds can be cut to size with a hacksaw.

#### Technical specifications:

- Maximum blind load weights:
  - Super lift 7kg 1:4 (if you pull the chain 20cm it will rise 5cm).

#### PRE-PACKED ROMAN BLIND SIZES

Code	Description	No. of cord spools	No. of brackets	Cord drop	Chain drop*
RBS060SU	60cm super lift pre-packed Roman blind kit	2	2	300cm	100cm
RBS090SU	90cm super lift pre-packed Roman blind kit	3	2	300cm	100cm
RBS120SU	120cm super lift pre-packed Roman blind kit	4	3	300cm	100cm
RBS150SU	150cm super lift pre-packed Roman blind kit	4	3	300cm	100cm
RBS180SU	180cm super lift pre-packed Roman blind kit	5	4	300cm	100cm
RBS240SU	240cm super lift pre-packed Roman blind kit	6	5	300cm	100cm

<sup>\*</sup> Alternative chains of 75cm, 125cm and 150cm can be purchased separately.





#### **ELECTRICALLY OPERATED BLINDS**

Within the MTM roman blind hardware offering, Hunter & Hyland also offer the option for electrically operated blinds. These are provided with all the same hardware as the MTM blind kits, but are also supplied with everything you need to operate your blind via a remote control.

- Max blind weight 4kg.
  Max width 200cm/ 5 cord spools
  Fitted "Forest" tubular motor 24v/16w 0.8NM
  Supplied with adapter and UK plug
  Remote control contains timer and can control up to 15 blinds
  10 year guarantee



#### TECHNICAL DIAGRAMS AND DATA

When you receive your Roman blind kit or components, you will also receive our Roman Blind System instruction sheet. This will take you through all the steps to not only ensure you have a fully child safety compliant blind system, but to also give you hints and tips to use all the elements to their optimum. The head rail is easy to assemble and fit and the instruction guide will cover any questions you might have throughout the processes of making and fitting your blind.

Technical information to note:


- The brackets supplied are designed to be able to be either wall (face) fixed or ceiling (top) fixed.
- The chain and cog are designed to breakaway from the main head rail if a force of 6kg or greater is applied. It can be re-inserted with a simple push and click.
- To maintain compliance with BSEN13120 regarding child safety; cord breakaways must be fitted if the distance between each fold is greater than 200mm (supplied with both made-to-measure and pre-packed kits).
- The chain drop has to be a minimum of 60cm from the floor to maintain compliance with BSEN13120.


The following diagrams show the headrail and bracket dimensions:


HEADRAIL DIMENSIONS

SPRING CLICK UNIVERSAL BRACKET DIMENSIONS

SWIVEL LOCK UNIVERSAL BRACKET DIMENSIONS







#### **Hunter & Hyland Ltd**

201a Kingston Road Leatherhead Surrey KT22 7PB

Tel: +44(0)1372 378511 Fax: +44(0)1372 370038

Email: sales@hunterandhyland.co.uk Website: www.hunterandhyland.co.uk

All trade enquiries from new clients should be accompanied by a PDF or fax of your company letterhead or business card.

#### **Trade counter**

Perfect for customers who want to choose and purchase products instantly. Help and advice is readily available.

Opening hours: between 8:30-13:00 and 14:00-16:45, Monday to Friday.

#### **Delivery**

We operate a small fleet of vans for deliveries in London and the South East. For all other areas, we provide a next day service via a trusted courier.

Hunter & Hyland Ltd T. +44(0)1372 378511 201a Kingston Road F. +44(0)1372 370038 Leatherhead, Surrey sales@hunterandhyland.co.uk KT22 7PB www.hunterandhyland.co.uk



